

SS5817 THRU SS5819

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIERS

Reverse Voltage – 20 to 40 Volts

Forward Current – 1.0 Ampere

Features

- Plastic package has Underwriters Laboratory Classification 94V-0
- Metal silicon junction, majority carrier conduction
- For surface mount applications
- Guard ring for overvoltage protection
- Low power loss, high efficiency
- High current capability, Low forward voltage drop
- High surge capability
- For use in low voltage, high frequency inverters, free wheeling , and polarity protection applications
- High temperature soldering guaranteed:250°C/10 seconds at terminals

Mechanical Data


- Case: JEDEC SMA(DO-214AC) molded plastic case
- Terminals: Solder plate, solderable per MIL-STD-750 MIL-STD -750, method 2026
- Polarity: Color band denotes cathode end
- Mounting Position: Any

Absolute Maximum Ratings and Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, resistive or inductive load. For capacitive load, derate by 20%.

	Symbols	SS5817	SS5818	SS5819	Units	
Maximum repetitive peak reverse voltage	V_{RRM}	20	30	40	Volts	
Maximum RMS voltage	V_{RMS}	14	21	28	Volts	
Maximum DC blocking voltage	V_{DC}	20	30	40	Volts	
Maximum non-repetitive peak reverse voltage	V_{RSM}	24	36	48	Volts	
Maximum average forward rectified current 0.375"(9.5mm) load length at $T_L = 90^\circ\text{C}$	$I_{(AV)}$		1		Amp	
Peak forward surge current 8.3mS single half sine-wave superimposed on rated load (JEDEC method) at $T_L = 70^\circ\text{C}$	I_{FSM}		25		Amps	
Maximum instantaneous forward voltage at 1.0 A (Note 1)	V_F	0.45	0.55	0.60	Volts	
Maximum instantaneous forward voltage at 3.1A (Note 1)	V_F	0.75	0.875	0.90	Volts	
Maximum instantaneous reverse current at rated DC blocking voltage (Note 1)	@ $T_A = 25^\circ\text{C}$	I_R	0.5			mA
	@ $T_A = 100^\circ\text{C}$		10			mA
Typical thermal resistance (Note 2)	$R_{\theta JA}$	88			$^\circ\text{C/W}$	
	$R_{\theta JL}$	28			$^\circ\text{C/W}$	
Typical junction capacitance (Note 3)	C_J	110			pF	
Operating and storage temperature range	T_J, T_S	-65 to +125			$^\circ\text{C}$	

SMA DO-214AC




Dimensions in mm

Notes: (1) Pulse test: 300μs pulse width, 1% duty cycle.

(2) Thermal Resistance (from Junction to Ambient) Vertical P.C.B Mounted, with 1.5x1.5" (38x38mm) copper pads.

(3) Measured at 1 MHz and reverse voltage of 4 volts.



РАДИОТЕХ-ТРЕЙД

Тел.: (495) 795-0805
Факс: (495) 234-1603
Эл. почта: info@rct.ru
Веб: www.rct.ru